




Product Data Sheet

GP LD GBM E14 4-40W 2-STEP FS CL

Order code	EAN	Packaging - SKU
085379-LDCE1	4986149085379	Eco blister, 1 pc/SKU
Product		
Category	LED Lamps	
Series	VINTAGE- 2-STEP FLAMESWITCH (FILAMENT)	
Model	MINI GLOBE FILAMENT 2-STEP FLAMESWITCH	
Description	GP LD GBM E14 4-40W 220-240V 2-STEP FLAMESWITCH CL	
General description		
Energy label	E	
Lamp shape	Mini Globe	
Lamp base	E14	
Dimmable	Yes	
Mercury free	Yes	
Mercury content	0.0 mg	
Recycling	Yes	
Electrical characteristics		
Nominal wattage	4.0 W \pm 10%	
Rated wattage	4.0 W	
Equivalent incandescent lamp power	40 W	
Power factor	$>$ 0.4	
Voltage	220-240 V	
Operating frequency	50/60Hz	
Lamp current	16-40 mA	
Weighted Energy Consumption	4 KWh / 1000 h	
Light technical characteristics		
Light colour	WARM WHITE	
Colour temperature	2200K 2700K	
Colour rendering index (Ra)	$>$ 80	
Colour consistency	$<$ 6 SDCM	
Nominal luminous flux	470 lm \pm 10%	
Rated luminous flux	470 lm	
Lumen maintenance factor at end of life	\geq 0.7	
Warm-up time (60%)	Instant s	
Starting time	$<$ 0.5s s	
Lifespan		
Nominal life time	15000 h	
Rated lamp life time	15000 h	
Switching cycles	50000	
Product dimensions		
Overall length (L)	79 mm \pm 1 mm	
Diameter (D)	45 mm \pm 1 mm	
Product Compliance		
	CE, ERP, ROHS, REACH	
Warranty		
	12 months from ex-factory date	



Spectral Distribution



- GP LED Lamps** are designed for true direct replacement of standard incandescent lamps.
- Compatible shapes and sizes of GLS
 - Very low energy consumption
 - Extremely long life
 - Emit a warm white or cold white light for different ambience
 - Instant start with full light output
 - Available in most common lamp bases for household use
 - No UV

Applications

- Domestic and commercial applications
- General illumination
- Can be used everywhere at home
- Use outdoors only in enclosed and ventilated luminaires